

Pull-out shelves 19"/4U

- Pull-out version 19"/4U
- Compatible with PoE, PoE+, PoE++
- Adjustable output voltage 48-56VDC
- SHELF-4U/IP-SU120
- Maximum power: 120W
- SHELF-4U/IP-SU240
- Maximum power: 240W



The 19" SHELF-4U/IP-SU racks are designed for fast and professional mounting of industrial LAN-RING switches and media converters in 19" racks. Included are guides to allow partial or complete removal of the shelf from the 19" rack.

Available models

| Order name | Order code |
|---------------------|------------|
| SHELF-4U/IP-SUP-PB7 | 4-500-017 |

Technical parameters**MECHANICS**

Number of positions for switch 1

Material AL sheet metal

Weight

Dimensions - h / w / d

Operating temperature -25...+70 °C

Standards and protocols

| Standard | Note |
|--------------|-----------------------|
| EN 55035 | Immunity requirements |
| EN 55032 | Emission requirements |
| EN 62368-1 | Safety requirements |
| EN IEC 63000 | ROHS |

EMC and safety

| Standard | Level | Note |
|------------------|-------|---|
| EN 61000-6-2 | | Immunity - industrial environment |
| IEEE 1613 | | Environmental and Testing Requirements Electric Power Substations |
| EN 50130-4 ed. 2 | | Alarm systems - Part 4: Electromagnetic compatibility |

Notes

- The manufacturer reserves the right to change technical parameters without prior notice.

Document created on 02/10/2026 05:46AM:09